







# OCL Essentials

ELIGIBLE SKU LIST | QUICK LEAD TIMES | SINGLE PAGE SPEC SHEETS

SERIES	MOUNTING	SIZE	DIFFUSER	FINISH 1	FINISH 2	LIGHT SOURCE	CCT	VOLTAGE	OAH	CONTROL	ESS OPTION
 <b>GS1 - GLOWSTICK</b>	P1CF	14	CR	BKP	N/A	LED1	(80+ CRI) 30K 35K 40K (90+ CRI) 930K 935K 940K	UNV	48	DM1	ESS
		18		MWP					100		
		24							144		
	P1FE	30									
		36									
 <b>GB1 - GLOWBALL</b>	P1CF	4	FS	BKP	N/A	LED1	(80+ CRI) 30K 35K 40K (90+ CRI) 930K 935K 940K	UNV	48	DM1	ESS
	P1FE			MWP					100		
	P1JA								144		
 <b>CT1 - CENTRO</b>	P1CF	14	MW	BKP	N/A	LED1	(80+ CRI) 30K 35K 40K (90+ CRI) 930K 935K 940K	UNV	48	DM1	ESS
				MWP		LED2			100		
 <b>LO1 - LOOP</b>	P1EC	14	MW	NFA	N/A	LED1	(80+ CRI) 30K 35K 40K (90+ CRI) 930K 935K 940K	UNV	48	DM1	ESS
	P1EM	24		BKP		LED2			100		
		36		MWP					144		
		48									
		72									
 <b>GL1 - GLOWRING</b>	P1EM	24	MW	NFA	N/A	LED1	(80+ CRI) 30K 35K 40K (90+ CRI) 930K 935K 940K	UNV	48	DM1	ESS
	P1EC	36		BKP					100		
		48		MWP					144		
		60									
		72									
	P1DA	24									
		36									
		48									
		60									
		72									
	P1DB	24									
		36									
		48									
		60									
	72										
 <b>NO1 - NOVA</b>	P1FA	18	MW	BKP	BKP	LED1	(80+ CRI) 30K 35K 40K (90+ CRI) 930K 935K 940K	UNV	48	DM1	ESS
		24		MWP	MWP	LED2			100		
		36							144		
	P1FB	18									
		24									
	36										

Please note that any additional colors, sizes, and/or options are not eligible for OCL Essentials pricing. Refer to ESSENTIALS specs sheets on the luminaire's product page for specification. Refer to full product specification sheet for full luminaire configuration options and detailed product specifications.