

PRECONFIGURED REV SHAPES SUBMITTAL WORKSHEET

CATALOG CODES

A	-	B	-	S	-	D	-	E	/	E	-	MW	-	G	-	/	-	UNV	-	J	-	DM1	-	L
SERIES	HANGING SYSTEM	CORD COLOR	SHAPE	SIZE 1 (LENGTH OR DIAMETER IN INCHES)	SIZE 2 (WIDTH IN INCHES)	DIFFUSER	FINISH					LIGHT SOURCE	VOLTAGE	OAH	CONTROL			OPTIONS						

SPECIFY CATALOG CODE		A		B		D		F		G	
Series	Hanging System	Shape	Diffuser	Finish							
 RV1S REV IN	P1DB PENDANT WITH ANGLED AIRCRAFT CABLES AND SILVER POWER CORD TO CANOPY WITH INTEGRAL DRIVER; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS)	REM RECTANGLE (MITERED)	MW MATTE WHITE	POWDER COAT FINISHES							
 RV2S REV OUT	P1EU PENDANT WITH 4 ANGLED AIRCRAFT CABLES AND SILVER POWER CORD TO CANOPY; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS); <u>REMOTE DRIVER ENCLOSURE</u>	TRM TRIANGLE (MITERED)	BKP BLACK								
 RV3S REV DOWN	P1EM PENDANT WITH VERTICAL AIRCRAFT CABLES TO SEPARATE MOUNTING POINTS AND SILVER POWER CORD TO CANOPY; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS); <u>REMOTE DRIVER ENCLOSURE</u>	PEM PENTAGON (MITERED)	BMP BRASS METALLIC								
 RV4S REV UP/DOWN	P1DA PENDANT WITH VERTICAL AIRCRAFT CABLES TO SEPARATE MOUNTING POINTS AND SILVER POWER CORD TO CANOPY WITH INTEGRAL DRIVER; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS)	HEM HEXAGON (MITERED)	BNP BRONZE								
	P1SC PENDANT WITH ANGLED AIRCRAFT CABLES AND SILVER POWER CORD TO <u>SQUARE</u> CANOPY; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS); <u>REMOTE DRIVER ENCLOSURE</u>	OCM OCTAGON (MITERED)	BTP BLACK TEXTURED								
	C1SF SEMI FLUSH CEILING MOUNT WITH 2" STANOFFS: <u>REMOTE DRIVER ENCLOSURE</u>	ANM 90° ANGLE (MITERED)	GRP GRAPHITE								
	S1SF SEMI FLUSH SURFACE MOUNT WITH 2" STANOFFS: <u>REMOTE DRIVER ENCLOSURE</u> (ADA COMPLIANT)	SQS SQUARE (SOFT)	GLP GOLDTASTIC								
		RES RECTANGLE (SOFT)	MWP MATTE WHITE								
		TRS ANGLE (SOFT)	SGP STEEL GRAY								
		PES PENTAGON (SOFT)	SMP SILVER METALLIC								
		HES HEXAGON (SOFT)	SWP SKY WHITE								
		OCS OCTAGON (SOFT)	WTP WHITE TEXTURED								
		ANS 90° ANGLE (SOFT)									
		1QA 90° ARC (QUARTER CIRCLE)	PREMIUM METAL FINISHES								
		2QR 90° DOUBLE SQUIGGLE RIGHT	BAL BRUSHED ALUMINUM								
		2QL 90° DOUBLE SQUIGGLE LEFT									
		3QA 90° TRIPLE SQUIGGLE	CUSTOM FINISHES								
		1HA 180° ARC (HALF CIRCLE)	RAL _____								
		2HR 180° DOUBLE ARC RIGHT	OTHER _____								
		2HL 180° DOUBLE ARC LEFT									
		3HA 180° TRIPLE ARC									
		RCT RACETRACK									
		ELP ELLIPSE									
C		D		E		F		G			
CORD COLOR		SIZE 1 (LENGTH OR DIAMETER IN INCHES)									
S SILVER BRAIDED POWER CORD				Indicate LENGTH/DIAMETER x WIDTH for your chosen shape. Squares, rectangles, angles, racetracks and ellipses will require two dimensions (SIZE 1 & SIZE 2). Straights, angles, squiggles & arcs, and polygons will only require one dimension (SIZE 1). See Page 6 for more details on calculating your fixture size.							

H			I	J	K	L
LIGHT SOURCE			VOLTAGE	OAH*	CONTROL	OPTIONS
LED OUTPUT LED1 LED2	COLOR TEMP (80+ CRI) 27K 30K 35K 40K	COLOR TEMP (90+ CRI) 927K 930K 935K 940K	UNV 120-277	48 100 144 NOTE: LEAVE BLANK WITH C1SF OR S1SF	DM1 0-10V DIMMING 1%	ULD DAMP LABEL BIOS BIOS SKYBLUE™ OR BIOS SKYBLUE™ DYNAMIC LIGHT ENGINE** PR4 4" SURFACE STANOFF (C1SF OR S1SF ONLY) PR6 6" SURFACE STANOFF (C1SF OR S1SF ONLY) MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)

SAMPLE CODE: RV3S-P1EM-SQS-1200-MW-WTP-LED1/935K-UNV-100-DM1

*For Minimum OAH, see hanging systems details. P1EM will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height. Note our minimum OAH is 8".

MODS, NOTES, & COMMENTS