

PRECONFIGURED REV SHAPES SUBMITTAL WORKSHEET

CATALOG CODES

A	-	B	-	S	-	D	-	E	/	E	-	MW	-	G	-	V	-	UNV	-	J	-	DM1	-	L
SERIES		HANGING SYSTEM		CORD COLOR		SHAPE		SIZE 1 (LENGTH OR DIAMETER IN INCHES)		SIZE 2 (WIDTH IN INCHES)		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		OAH		CONTROL		OPTIONS

SPECIFY CATALOG CODE

A	B	D	F	G		
SERIES	HANGING SYSTEM	SHAPE	DIFFUSER	FINISH		
 RV1S REV IN RV2S REV OUT RV3S REV DOWN RV4S REV UP/DOWN	P1DB PENDANT WITH ANGLED AIRCRAFT CABLES AND SILVER POWER CORD TO CANOPY WITH INTEGRAL DRIVER; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS)	REM RECTANGLE (MITERED) TRM TRIANGLE (MITERED) PEM PENTAGON (MITERED) HEM HEXAGON (MITERED) OCM OCTAGON (MITERED) ANM 90° ANGLE (MITERED) SQS SQUARE (SOFT) RES RECTANGLE (SOFT) TRS ANGLE (SOFT) PES PENTAGON (SOFT) HES HEXAGON (SOFT) OCs OCTAGON (SOFT) ANS 90° ANGLE (SOFT) 1QA 90° ARC (QUARTER CIRCLE) 2QR 90° DOUBLE SQUIGGLE RIGHT 2QL 90° DOUBLE SQUIGGLE LEFT 3QA 90° TRIPLE SQUIGGLE 1HA 180° ARC (HALF CIRCLE) 2HR 180° DOUBLE ARC RIGHT 2HL 180° DOUBLE ARC LEFT 3HA 180° TRIPLE ARC RCT RACETRACK ELP ELLIPSE	MW MATTE WHITE	POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED PREMIUM METAL FINISHES BAL BRUSHED ALUMINUM CUSTOM FINISHES RAL _____ OTHER _____		
	PIEU PENDANT WITH 4 ANGLED AIRCRAFT CABLES AND SILVER POWER CORD TO CANOPY; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS); <u>REMOTE DRIVER ENCLOSURE</u>	PIEM PENDANT WITH VERTICAL AIRCRAFT CABLES TO SEPARATE MOUNTING POINTS AND SILVER POWER CORD TO CANOPY; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS); <u>REMOTE DRIVER ENCLOSURE</u>	PIDA PENDANT WITH VERTICAL AIRCRAFT CABLES TO SEPARATE MOUNTING POINTS AND SILVER POWER CORD TO CANOPY WITH INTEGRAL DRIVER; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS)	PISC PENDANT WITH ANGLED AIRCRAFT CABLES AND SILVER POWER CORD TO <u>SQUARE CANOPY</u> ; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS); <u>REMOTE DRIVER ENCLOSURE</u>	CISF SEMI FLUSH CEILING MOUNT WITH 2" STANDOFFS; <u>REMOTE DRIVER ENCLOSURE</u>	SISF SEMI FLUSH SURFACE MOUNT WITH 2" STANDOFFS; <u>REMOTE DRIVER ENCLOSURE</u> (ADA COMPLIANT)
	C		E			
	CORD COLOR		SIZE 1 (LENGTH OR DIAMETER IN INCHES)			
	S SILVER BRAIDED POWER CORD	Indicate LENGTH/DIAMETER x WIDTH for your chosen shape. Squares, rectangles, angles, racetracks and ellipses will require two dimensions (SIZE 1 & SIZE 2). Straights, angles, squiggles & arcs, and polygons will only require one dimension (SIZE 1). See Page 6 for more details on calculating your fixture size.				

H		I		J	K		L	
LIGHT SOURCE		VOLTAGE		OAH*	CONTROL		OPTIONS	
LED OUTPUT LED1 LED2	COLOR TEMP (80+ CRI) 27K 30K 35K 40K	COLOR TEMP (90+ CRI) 927K 930K 935K 940K	UNV 120-277	48 100 144 NOTE: LEAVE BLANK WITH CISF OR SISF	DM1 0-10V DIMMING 1%	ULD DAMP LABEL BIOS BIOS SKYBLUE™ OR BIOS SKYBLUE™ DYNAMIC LIGHT ENGINE** PRA 4" SURFACE STANDOFF (CISF OR SISF ONLY) PRB 6" SURFACE STANDOFF (CISF OR SISF ONLY) MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)		

SAMPLE CODE: SL1S-PXXEMW-SQM-36/48-MW-WTP-LED1/35K-UNV-100-DM1

*For Minimum OAH, see hanging systems details. PIEM will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height. Note our minimum OAH is 8".

MODS, NOTES, & COMMENTS

