



PROJECT NAME: _____ TYPE: _____

QTY: _____

GLOWSTICK SIGNATURE CLUSTER SUBMITTAL WORKSHEET



CATALOG CODES

GS1C	-	P	B	XX	-	S	-	D	-	E	/	E	-	F	-	CR	-	H	-	LED1	/	-	UNV	-	K	-	DMO	-	MOD
SERIES		HANGING SYSTEM				CORD COLOR		CANOPY SHAPE		SIZE 1 (LENGTH OR DIAMETER IN INCHES)		SIZE 2 (WIDTH IN INCHES; LEAVE BLANK FOR CIRCLES)		DROP PATTERN		DIFFUSER		FINISH		LIGHT SOURCE			VOLTAGE		OAH		CONTROL		OPTIONS

SPECIFY CATALOG CODE															
A	B	C	D	E	F	G	H								
SERIES	HANGING SYSTEM	CORD COLOR	CANOPY SHAPE	SIZE 1 / SIZE 2 (LENGTH OR DIAMETER IN INCHES / WIDTH IN INCHES)	DROP PATTERN	DIFFUSER	FINISH								
GS1C GLOWSTICK	P__XX SPECIFY NUMBER OF DROPS	S SILVER BRAIDED POWER CORD	SQM SQUARE CANOPY REM RECTANGLE CANOPY RND CIRCLE CANOPY ELP ELLIPSE CANOPY	List your length (SIZE 1) and width (SIZE 2) for squares, rectangles or ellipses. List diameter (SIZE 1) and leave (SIZE 2) blank for circles. See Page 10 for more details on calculating your canopy size.	LVL LEVEL PATTERN STP STEPPED PATTERN WVE WAVE PATTERN SWO SWOOP PATTERN RDM RANDOM PATTERN CST CUSTOMER SPECIFIED PATTERN Choose the Level (LVL) pattern at your longest overall height (OAH) to configure your pattern in the field.	CR 12" CLEAR ACRYLIC ROD NOTE: ADDITIONAL LENGTHS MAY BE SPECIFIED; CONTACT FACTORY	POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED PREMIUM METAL FINISHES BAL BRUSHED ALUMINUM CUSTOM FINISHES RAL _____ OTHER _____								

I			J	K	L	M
LIGHT SOURCE			VOLTAGE	OAH	CONTROL	OPTIONS
LED OUTPUT LED1	COLOR TEMP (80+ CRI) 27K 30K 35K 40K	COLOR TEMP (90+ CRI) 927K 930K 935K 940K	UNV 120-277	SPECIFY IN INCHES (NOTE: MINIMUM OAH IS 54"; DROPS ARE FIELD ADJUSTABLE))	DMO 0-10V DIMMING 10%	MOD MODIFIED LUMINAIRE

SAMPLE CODE: GS1C-P36XXS-SQM-36/48-LVL-MW-BTP-LED1/935K-UNV-144-DM1-MOD

MODS, NOTES, & COMMENTS

LUMENS & WATTAGE CHART		PER DROP
LED1	LUMENS DELIVERED	350
	SYSTEM WATTAGE	5
CUSTOM LUMEN PACKAGES AVAILABLE		